DECLARATION OF PERFORMANCE

According to Regulation (EU) n°305/2011

Unique identifier code for product-type / N° :	5-RPC2020/12/30		して		
Model :	AGORAFOCUS 630				
Intented uses of the product in accordance with the applicable harmonised technical specification :	Roomheater burning solid fuel without hot water supply				
Manufacturer :	Atelier Dominique Imbert s.a.s. 3 Impasse Claque Patin 34380 Viols le Fort	3 Impasse Claque Patin			
Assessment and verification system for constancy of performance :	System 3				
Notified body :	Istituto Giordano S.p.A., Nº 0407				
Test report number (based on System 3) :	Ist. Giordano – 378788/13833/CPR				
Declared performance :					
Harmonised technical specification :	EN 13240:2001/A2:2004/AC:2007				
Reaction to fire	Al				
Distance to combustible material	Rear	80	cm		
	Side	80	cm		
	Front	80	cm		
	Floor	/	cm		
Risk of burning fuel falling out	Pass				
Emissions of combustion products	CO	0,09	%		
	Dust	20	mg/m ³		
	OGC	56	mg/m ³		
	NO	71			

NOx71mg/rSurface temperaturePassCleanabilityPassFlue gas temperature (Nominal heat output)255°CMechanical resistance (to carry a chimney/flue)NPDNominal heat output18,5kWRoom heating output-kW		Dust	20	mg/m
Surface temperature Pass Cleanability Pass Flue gas temperature (Nominal heat output) 255 °C Mechanical resistance (to carry a chimney/flue) NPD Nominal heat output 18,5 kW Room heating output - kW		OGC	56	mg/m ³
Cleanability Pass Flue gas temperature (Nominal heat output) 255 °C Mechanical resistance (to carry a chimney/flue) NPD Nominal heat output 18,5 kW Room heating output - kW		NOx	71	mg/m ³
Flue gas temperature (Nominal heat output) 255 °C Mechanical resistance (to carry a chimney/flue) NPD 18,5 kW Nominal heat output 18,5 kW	Surface temperature	Pass		
Mechanical resistance (to carry a chimney/flue) NPD Nominal heat output 18,5 kW Room heating output - kW	Cleanability	Pass		
Nominal heat output 18,5 kW Room heating output - kW	Flue gas temperature (Nominal heat output)		255	°C
Room heating output - kW	Mechanical resistance (to carry a chimney/flue)	NPD		
	Nominal heat output		18,5	kW
Efficiency 81,0 %	Room heating output		-	kW
	Efficiency		81,0	%

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Laurent Gaborit Directeur Général

E

Signature :

Viols le Fort, le 15 avril 2021