

Regulation No. 305/2011 DOP-Scan-Line 800-1447 Rev. 4-2017

| Unique identification code of product-type | Stove |
|---|---|
| 2. Product name | Scan-Line 800, 810, 820, 830, 840, 850, 80, 80XL, 800M series |
| Intended use or uses of the construction product, in accordance with the applicable technical specification | Room heater burning solid fuel without hot water supply |
| 4. Name and contact address of the manufacturer | Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk |
| 5. Where applicable, name and contact address of authorized representative. E-mail. | Factory Manager Martin Bach, E-mail: martin.bach@heta.dk |
| 6. System of assessment and verification of constancy of performance of the construction product | System 3 |
| 7. Notified body relevant to the assessment and verification of constancy of performance | Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-1447-EN-Rev-4 |

8. Declared Performance

| Harmonized technical specification | EN 13240:2001/A2:20 | 04 |
|------------------------------------|---|--|
| Emission | CO Nox Dust Dust (NS3058/3059) OGC (CEN/TS 15883) | 0,06% / 705mg/Nm³ 85 mg/Nm³ 24 mg/Nm³ 2,61 g/kg 48 mgC/Nm³ at 13% O ₂ |

Fire safety

| Reaction to fire | A1 |
|---|---|
| Test of fire safety in connection with the burning of wood | Approved |
| Distance to combustible materials Rear Sides distance to combustible materials Distance to floor from lower edge of the door Furniture distance | Minimum distances in mm 125 300 (340 for the M-series) 900 |

Safety

| Mechanical resistance (to carry a chimney / flue) | Not tested (NPD) |
|---|------------------------|
| Electrical safety | NA (NPD) |
| Surface temperature | Approved |
| Cleanability | No specification (NPD) |

Thermal output

| Nominal heat output | 6,8 kW |
|--|--------------|
| Room heat output | 6,8 kW |
| Energy efficiency | η 81% |
| Fluegas temperature at nominal heat output | T 267°C |
| Water heating output | NA (NPD) |
| Maximum water operating pressure | NA (NPD) |

9.

The performance of the product identified in points1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer.

anguacturer of 03.01.2023

TLF. 45 9663 0600

DK-7620 LEMVIG

FAX +45 9663 0616