

# **Ecodesign EU Declaration of Conformity**

DoC Scan-Line 500 2354-2018

# **Product fiche**



Manufacturer	Heta A/S	
Adress	Jupitervej 22, DK 7620 Lemvig	
E-mail	heta@heta.dk	
Website	www.heta.dk	
Telephone	+45 9663 0600	

Scan-Line 500, 510, 520, 520B, 550, 551, 560B, 560S, 590, Turin, Turin B, Napoli, 10-20-20B-30-30B, Tour Model identifier 10-20-30, 40-40B-50-50B serie

The identified product described above is in

conformity with:	
The relevant EU harmonized regulations:	

DIR 2009/125/EF

REG (EU) 2015/1185

REG (EU) 2015/1186

REG (EU) 2017/1369

REG (EU) 305/2011

### The relevant harmonized standards

EN 13240:2001/A2:2004

CEN/TS 15883:2010

## Characteristics when operating with the preferred fuel only

### **Heat output**

Item	Symbol	Value/Unit		
Nominal heat output	P <sub>nom</sub>	6,1 kW		
Minimum heat output	P <sub>min</sub>			
Useful efficiency (NCV as received)				
Useful efficiency at nominal heat output	η <sub>th, nom</sub>	82%		
Useful efficiency at minimum heat output	η <sub>th, min</sub>			
Auxiliary electricity consumption				

At nominal heat output	el <sub>max</sub>	- kW
At minimum heat output	el <sub>min</sub>	- kW
In standby mode	el <sub>sв</sub>	- kW

## Type of heat output/room temperature control

single stage heat output, no room temperature control	Yes
two or more manual stages, no room temperature control	No
with electronic room temperature contro	No
with electronic room temperature control	No
with electronic room temperature control plus day timer	No
with electronic room temperature control plus week timer	No

# Other control options

room temperature control, with presence detection	
room temperature control, with open window detection	
with distance control option	No

## Notified body relevant to the assessment and verification of constancy of performance

Danish Technological Institute, DK-8000 Aarhus No. 1235. Report no. 300-ELAB-2354-EN

Fuel	Preferred fuel	Other suit- able fuel
Wood logs with moisture content ≤ 25 %	Yes	No
Compressed wood with moisture content < 12 %	No	No
Other woody biomass	No	No
Non-woody biomass	No	No
Anthracite and dry steam coal	No	No
Hard coke	No	No
Low temperature coke	No	No
Bituminous coal	No	No
Lignite briquettes	No	No
Peat briquettes	No	No
Blended fossil fuel briquettes	No	No
Blended biomass and fossil fuel briquettes	No	No
Other blend of biomass and solid fuel	No	No

Emissions at		mg/Nm³ (13 % O <sub>2</sub> )			
nominal heat output	<b>η</b> <sub>s</sub> %	PM	OGC	СО	NO <sub>x</sub>
output	≥ 65	≤ 40	≤ 120	≤ 1500	≤ 200
	72	16	50	558	90

Technical documentation	
Indirect heating functionality:	No
Direct heat output:	6,1 kW
Energy Efficiency Index (EEI):	EEI 109
Fluegas temperature at nominal heat output	T 243°C
Energy efficiency class	$A^{+}$

Safty	
Reaction to fire	A1
Test of fire safety in connection with the burning of wood	Approved
Distance to combustible materials Rear. Without insulation / with insulation Sides distance to combustible materials Furniture distance	Minimum distances in mm 150 350 1000

Signed on behalf the manufacturer of 07.02.2022



Signature