EN



## Ecodesign EU Declaration of Conformity

DoC Scan-Line 7 2534-2020 Product fiche



| Manufacturer | Heta A/S                      |
|--------------|-------------------------------|
| Adress       | Jupitervej 22, DK 7620 Lemvig |
| E-mail       | heta@heta.dk                  |
| Website      | www.heta.dk                   |
| Telephone    | +45 9663 0600                 |

| Ī | VI | o | d | ۵  | ١i | d | ei | ni | Hif | Fi | er  |  |
|---|----|---|---|----|----|---|----|----|-----|----|-----|--|
| ш | VΙ | v | u | C. |    | u | CI | ш  | ш   | ш  | CI. |  |

Scan-Line 7B, 7C, 7D, 7L serie

| The identified product described above is in conformity with: |  |  |  |
|---|--|--|--|
| The relevant EU harmonized regulations:                       |  |  |  |
| DIR 2009/125/EF   |  |  |  |
| REG (EU) 2015/1185  |  |  |  |
| REG (EU) 2015/1186  |  |  |  |
| REG (EU) 2017/1369  |  |  |  |
| REG (EU) 305/2011   |  |  |  |
|   |  |  |  |

## The relevant harmonized standards

**Auxiliary electricity consumption** 

At nominal heat output

At minimum heat output

In standby mode

EN 13240:2001/A2:2004

CEN/TS 15883:2010

## fuel only **Heat output** Item Symbol Value/Unit 4 kW Nominal heat output $\overline{P_{\underline{\text{min}}}}$ Minimum heat output Useful efficiency (NCV as received) Useful efficiency at nominal heat 83% $oldsymbol{\eta}_{ ext{th, nom}}$ output Useful efficiency at minimum heat ${\pmb \eta}_{\rm th,\,min}$ output

Characteristics when operating with the preferred

| Type of heat output/room temperature control             |     |  |  |
|--|-----|--|--|
| single stage heat output, no room temperature control    | Yes |  |  |
| two or more manual stages, no room temperature control   | No  |  |  |
| with electronic room temperature contro                  | No  |  |  |
| with electronic room temperature control                 | No  |  |  |
| with electronic room temperature control plus day timer  | No  |  |  |
| with electronic room temperature control plus week timer | No  |  |  |

 $el_{mir}$ 

else

- kW - kW

- kW

| Other control options                                |    |  |  |  |
|--|----|--|--|--|
| room temperature control, with presence detection    | No |  |  |  |
| room temperature control, with open window detection | No |  |  |  |
| with distance control option                         | No |  |  |  |

## Notified body relevant to the assessment and verification of constancy of performance

Danish Technological Institute, DK-8000 Aarhus No. 1235. Report no. 300-ELAB-2534-EN

| Fuel   | Preferred fuel | Other suit-<br>able fuel |
|--|----------------|--------------------------|
| Wood logs with moisture content ≤ 25 %       | Yes            | No                       |
| Compressed wood with moisture content < 12 % | No             | No                       |
| Other woody biomass                          | No             | No                       |
| Non-woody biomass                            | No             | No                       |
| Anthracite and dry steam coal                | No             | No                       |
| Hard coke                                    | No             | No                       |
| Low temperature coke                         | No             | No                       |
| Bituminous coal                              | No             | No                       |
| Lignite briquettes                           | No             | No                       |
| Peat briquettes                              | No             | No                       |
| Blended fossil fuel briquettes               | No             | No                       |
| Blended biomass and fossil fuel briquettes   | No             | No                       |
| Other blend of biomass and solid fuel        | No             | No                       |

| Emissions at        |                         | mg/Nm³ (13 % O <sub>2</sub> ) |       |        |                 |  |  |
|---------------------|-------------------------|-------------------------------|-------|--------|-----------------|--|--|
| nominal heat output | <b>η</b> <sub>s</sub> % | PM                            | OGC   | СО     | NO <sub>x</sub> |  |  |
| output              | ≥ 65                    | ≤ 40                          | ≤ 120 | ≤ 1500 | ≤ 200           |  |  |
|                     | 73                      | 15                            | 90    | 1009   | 78              |  |  |

| Technical documentation                    |         |
|--|---------|
| Indirect heating functionality:            | No      |
| Direct heat output:                        | 4 kW    |
| Energy Efficiency Index (EEI):             | EEI 110 |
| Fluegas temperature at nominal heat output | T 243°C |
| Energy efficiency class                    | $A^{+}$ |

| Safty   |  |
|---|--|
| Reaction to fire  | A1   |
| Test of fire safety in connection with the burning of wood  | Approved                                     |
| Distance to combustible materials Rear. Without insulation / with insulation Sides distance to combustible materials Furniture distance | Minimum distances in mm<br>100<br>100<br>800 |

Signed on behalf the manufacturer of 07.02.2022



| The chimney sweep's signature | Date |
|-------------------------------|------|
|                               |      |

Signature